

LEDdrive 3/6 Desktop

Constant Current 0-10V

Data Sheet



Product Overview

LEDdrive 3/6 is a Desktop LED controller for 350mA (1 Watt) or 700mA (3 watt) constant current LED's. This unit is controlled via analogue 0-10V allowing integration with analogue systems.

LEDdrive 3/6 can be supplied with an external 12 - 48VDC power supply.

Features

- 0-10VDC control input
- External Power Supply 12 - 48 VDC
- Terminal Strip Output and Input Connector
- 2 Main indication LEDs

Technical Data

Input voltage	12 - 48VDC
Power supply	External
Total driver power	Up to 216W
Dimension	105mm (L) x 105mm (W) x 55mm (H)
Mounting method	Desktop
Control input	Terminal block
Output channels	3 or 6ch
Colour grades	256 level (each colour) total 16,770,000 colours
Driving capacity	350mA/700mA per channel
Temperature	0 – 40 degree Celsius

Melbourne
138-146 Browns Road
Noble Park 3174
Victoria Australia

Tel 03 9701 2500
Fax 03 9701 2511

Sydney
18 Fariola Street
Silverwater 2128
NSW Australia

Tel 02 9737 8988
Fax 02 9737 8388

lightmoves
illuminating ideas

www.lightmoves.com.au
ABN 22 529 618 235