



Date: _____ Type: _____

Firm Name: _____

Project: _____

eW Graze Powercore Family

Linear exterior LED wall grazing fixtures with solid white light

Custom Configurations

Select one component from each column to specify a complete configuration.

Fixture Length	Color Temp. / Color	Beam Angle*	Housing Color
1 ft	2700 K	9° x 9°	RAL 9006
2 ft	3000 K	10° x 60°	Any RAL CLASSIC color except whites
3 ft	3500 K	15° x 30°	
4 ft	4000 K	30° x 60°	
	5500 K	60° x 30°	
	6500 K	60° x 60°	
	Royal Blue	60° x 90°	
		90° x 60°	

= Standard component

* MX / QLX / QLX 5W only.

Limited quantity of samples available.

Standard Configurations

If you select all standard components (shaded green), find your configuration in the standard configurations list, and order using the Item Number or Philips 12NC. Standard configurations are not subject to minimum order quantities or extended production lead times.

Standard Configuration Example:

eW Graze MX Powercore, 1 ft, 2700 K, 10° x 60°

(Use Item Number 523-000080-03 or Philips 12NC 910503703690)

Custom Configurations

If you select one or more non-standard (non-shaded) components, your configuration is custom.

Custom Minimum Order Quantity: 100 ft total, any mix of fixture lengths

Custom Production Lead time: 12 weeks ARO (standard shipping options apply)

Custom Configuration Example:

Special, eW Graze QLX Powercore, 3 ft, 6500 K, 90° x 60°, RAL 3028

In North America contact: Philips Color Kinetics Sales, 888.385.5742 or sales@colorkinetics.com

(Contact your Philips Color Kinetics Lighting Sales group with the product description for custom configurations.)

PHILIPS

Accessories

Item	Type		Item Number	Philips 12NC
Leader Cable with Terminator	UL / cUL	10 ft (3.0 m)	108-000056-03	910503704071
		50 ft (15.2 m)	108-000056-00	910503703138
	CE / PSE	10 ft (3.0 m)	108-000056-04	910503704072
		50 ft (15.2 m)	108-000056-01	910503704069
Jumper Cable	UL / cUL	End-to-End	108-000057-00	910503703139
		1 ft (305 mm)	108-000057-03	910503704076
		5 ft (1.5 m)	108-000057-06	910503704079
		10 ft (3.0 m)	108-000057-09	910503704082
		End-to-End	108-000057-01	910503704074
	CE / PSE	1 ft (305 mm)	108-000057-04	910503704077
		5 ft (1.5 m)	108-000057-07	910503704080
		10 ft (3.0 m)	108-000057-10	910503704083
		1 ft (305 mm)	120-000081-00	910503700745
		2 ft (610 mm)	120-000081-01	910503700746
Glare Shield	3 ft (914 mm)	120-000081-02	910503700747	
	4 ft (1219 mm)	120-000081-03	910503700748	
	Additional Terminators	Quantity 10	120-000157-00	910503703142
Additional Hinge	Quantity 1	120-000098-00	910503700772	

Use Item Number when ordering in North America.

OPTIBIN® | POWERCORE® | DIMAND®
CK TECHNOLOGY | CK TECHNOLOGY | CK TECHNOLOGY

* For information on how to buy Philips Color Kinetics LED lighting systems, visit www.philipscolorkinetics.com/ls/howtobuy/

Features

The new eW Graze Powercore family dramatically extends the range and flexibility of the popular line of solid white light LED grazing fixtures from Philips Color Kinetics. Featuring Powercore technology, eW Graze Powercore fixtures process power directly from line voltage, eliminating the need for external power supplies. Fixtures are available in standard color temperatures of 2700 K, 4000 K, and 5500 K, with additional custom color temperatures available, ranging from 3000 K to 6500 K. Multiple fixture lengths, beam angles, output levels, and power consumption levels support a large range of façade or surface illumination application. Low-profile housing, connectorized cabling, a universal power input range, and direct line-voltage operation make eW Graze Powercore fixtures easy to install and operate.

- Tailor light output to specific applications
- High-performance illumination and beam quality
- Superior color consistency and accuracy
- Line-voltage operation
- Universal power input range
- Versatile installation options
- “Cool lighting” functionality
- Dimming capability

For detailed product information, please refer to the eW Graze Powercore Family Product Guide at www.philipscolorkinetics.com/ls/essentialwhite/ewgrazemxpowercore/



Philips Color Kinetics
3 Burlington Woods Drive
Burlington, Massachusetts 01803 USA
Tel 888.385.5742
Tel 617.423.9999
Fax 617.423.9998
www.philipscolorkinetics.com

Copyright © 2013 Philips Solid-State Lighting Solutions, Inc. All rights reserved.
Chromacore, Chromasic, CK, the CK logo, Color Kinetics, the Color Kinetics logo, ColorBlast, ColorBlaze, ColorBurst, eW Fuse, ColorGraze, ColorPlay, ColorReach, iW Reach, eW Reach, DIMand, EssentialWhite, eVW, iColor, iColor Cove, IntelliWhite, iW, iPlayer, Optibin, and Powercore are either registered trademarks or trademarks of Philips Solid-State Lighting Solutions, Inc. in the United States and / or other countries. All other brand or product names are trademarks or registered trademarks of their respective owners. Due to continuous improvements and innovations, specifications may change without notice. DAS-000117-71 R00 04-13