



Date: \_\_\_\_\_ Type: \_\_\_\_\_

Firm Name: \_\_\_\_\_

Project: \_\_\_\_\_

# eW Reach Compact Powercore UL / CE

Premium long-throw compact exterior LED floodlight with solid white light

## Ordering Information

Select a color or color temperature to specify a complete configuration.

### Color / Color Temp

Royal Blue

2700 K

3000 K

3500 K

4000 K

5000 K

5500 K

6000 K

6500 K

= Standard component

### Standard Configuration

If you select a color temperature of 2700 K or 4000 K, your eW Reach Compact Powercore configuration is standard. Order a standard configuration using Item Number or Philips 12NC. Standard configurations are not subject to a minimum order quantities or extended production lead times.

#### Standard Configuration:

eW Reach Compact Powercore, 4000 K, UL

Use Item Number 523-000095-03 or Philips 12NC 912400130213 (UL)

Use Item Number 523-000095-09 or Philips 12NC 912400130231 (CE)

### Custom Configurations

If you select a color temperature other than 2700 K or 4000 K, your configuration is custom.

Minimum Order Quantity: 20 fixtures for each custom configuration

Production Lead time: 12 weeks ARO (standard shipping options apply)

#### Custom Configuration:

Special, eW Reach Compact Powercore, 3000 K, CE

(Contact your Philips Lighting Sales group with the product description for custom configurations.)

In North America contact: Philips Color Kinetics Sales, 888.385.5742 or sales@colorkinetics.com



## eW Reach Compact Powercore Standard Configurations

Item	Type	Item Number	Philips 12NC
eW Reach Compact Powercore Includes 10 ft (3.0 m) Leader Cable	2700 K	UL / cUL	523-000095-00 910503703281
		CE / PSE	523-000095-06 912400130228
	4000 K	UL / cUL	523-000095-03 912400130225
		CE / PSE	523-000095-09 912400130231



CHROMACORE<sup>®</sup> | OPTIBIN<sup>®</sup> | POWERCORE<sup>®</sup>  
CK TECHNOLOGY | CK TECHNOLOGY | CK TECHNOLOGY

## Accessories

Item	Type	Item Number	Philips 12NC
3 Conductor Replacement Leader Cable:	10 ft (3.0 m)	UL / cUL	108-000056-03 910503704071
		CE / PSE	108-000056-04 910503704072
	50 ft (15.2 m)	UL / cUL	108-000056-00 910503703138
		CE / PSE	108-000056-01 910503704069
4 Conductor Replacement Leader Cable: (required to digitally dim unit, w/ DE Pro)	10 ft (3.0 m)	UL / cUL	108-000055-03 910503704066
		CE / PSE	108-000055-04 910503704067
	50 ft (15.2m)	UL / cUL	108-000055-00 910503703137
		CE / PSE	108-000055-01 910503704064
Data Enabler Pro (required to digitally dim unit)	3/4 in / 1/2 in NPT (US trade size conduit)	106-000004-00	910503701210
	PG21 / PG13 (metric size conduit)	106-000004-01	910503701211
Spread Lens with bezel	8°	120-000068-05	910503700511
	13°	120-000068-00	910503700506
	23°	120-000068-01	910503700507
	40°	120-000068-02	910503700508
	63°	120-000068-03	910503700509
	Asymmetric (5° x 17°)	120-000068-04	910503700510

Use Item Number when ordering in North America.

\* For more information on how to buy Philips Color Kinetics LED lighting systems, visit [www.philipscolorkinetics.com/ls/howtobuy/](http://www.philipscolorkinetics.com/ls/howtobuy/)



Philips Color Kinetics  
3 Burlington Woods Drive  
Burlington, Massachusetts 01803 USA  
Tel 888.385.5742  
Tel 617.423.9999  
Fax 617.423.9998  
[www.philipscolorkinetics.com](http://www.philipscolorkinetics.com)  
@ColorKinetics

Copyright © 2012 – 2104 Philips Solid-State Lighting Solutions, Inc. All rights reserved.  
Chromacore, Chromasic, CK, the CK logo, Color Kinetics, the Color Kinetics logo, ColorBlast, ColorBlaze, ColorBurst, eW Fuse, ColorGraze, ColorPlay, ColorReach, iW Reach, eW Reach, DIMand, EssentialWhite, eW, iColor, iColor Cove, IntelliWhite, iW, iPlayer, Optibin, and Powercore are either registered trademarks or trademarks of Philips Solid-State Lighting Solutions, Inc. in the United States and / or other countries. All other brand or product names are trademarks or registered trademarks of their respective owners. Due to continuous improvements and innovations, specifications may change without notice.

DAS-000140-08 R00 08-14

## Features

eW Reach Compact Powercore combines all the benefits of LED-based lighting in a compact fixture specifically designed for large-scale installations calling for high-quality white light, including commercial skyscrapers, casinos, large retail exteriors, bridges, piers, public monuments, and themed attractions. With levels of light output and projection never before achieved in a compact LED lighting fixture, eW Reach Compact Powercore delivers intense, energy-efficient output at a reasonable price, opening up new possibilities for exterior illumination. Standard configurations include a warm 2700 K and a cool 4000 K, with six additional color temperatures available, ranging from 3000 K to 6500 K.

- Unique split design supports diffuser combinations
- Unparalleled light output of over 10,000 lumens
- Universal power input range, directly from line voltage
- Exchangeable spread lenses of 8°, 13°, 23°, 40°, 63°, and an asymmetric 5° x 17°
- Simple fixture positioning
- Industry-leading control

For detailed product information, please refer to the eW Reach Compact Powercore Product Guide at [www.philipscolorkinetics.com/ls/essentialwhite/ewreachcompact/](http://www.philipscolorkinetics.com/ls/essentialwhite/ewreachcompact/)