

Apollo

lightsource for indoor
dry locations



Utilising the very latest in high output fibre optic 150w CDM lamp technologies, together with electronic lamp and fan control for maximum performance and reliability.

Precision optical chassis.

A low cost, no compromise, versatile lightsource.



Typical Applications

- For Sidelight and Endlight applications
- Ideal for residential situations - home theatre, star fields, bar top/wine rack lighting, accent/feature lighting, decorative displays.
- Display cabinet/conservation lighting.

Versions

| | |
|-----------------|--------------------------------------|
| APOLLO-INT-500 | 500 x .75mm fibres. |
| APOLLO-INT-1000 | 1000 x .75mm fibres (Future release) |

Specifications

| | |
|---------------------|--|
| Electrical | 230/240V 50/60Hz. Electronic control gear. |
| Construction | Powder coated aluminium base and lid. |
| Dimensions | 295L x 220W x 150H |
| Mounting position | Universal. |
| Weight | 3kg |
| Environment | Maximum ambient operating temp. 40°C |
| Ventilation | High throughput DC fan for cooling |
| Filters | UV and IR. |
| Fibre capacity | APOLLO-500 500 x 0.75mm fibres recommended position for side or endlight APOLLO-1000 1000 x 0.75mm fibres recommended position for endlight only. |
| Fibre terminations | Hot Knife |
| Optical performance | APOLLO-500 4.0 lumens per 0.75mm fibre. APOLLO-1000 3.0 lumens per 0.75mm fibre. (measured outputs at 2M length) |
| Colour wheel | Dichroic glass. (Green, Orange, White, Blue, Yellow, Pink). 1 RPM motor. |
| Motor switch | Standard. |
| Options | Synchronisation. 2.4, 3.3, 4.2 RPM motors. Custom colour wheels, scintillation wheels. Single wheel DMX (Future release) |

DIGILINAUSTRALIA
37 Oxford Street
Bulimba
Qld 4171
Australia
Ph 61 7 3899 1267
Fax 61 7 3899 1261
sales@digilin.com.au
www.digilin.com.au

F
I
B
R
E

O
P
T
I
C

L
I
G
H
T
I
N
G

8/2/06

For more information please contact

lightmoves (03) 9701 2500
info@lightmoves.com.au

138-146 Browns Rd, Noble Park VIC 3174

Fibre Optic Lighting Technologies