## **FREEDOM**

High Performance LED Downlight 4647 - 6334 Lumens











## An LED alternative with high output and low glare

An outstanding commercial, retail, and theatrical downlight, using the latest technology from Digilin. Amazing efficiency and massive lumens are what you get from the Freedom LED downlight.

Designed for high ceiling applications such as showrooms, shopping centres and auditoriums, the Freedom LED downlight allows LED efficiency and longevity into projects which have historically relied upon halogen and metal halide.





## **SPECIFICATIONS**

| Version         Freedom 1440         Freedom 150           Colours         Warm White         Neutral White         Cool White         Warm White         Neutral White         Cool White           Colour Temperature         3000K         4000K         5000K         3000K         4000K         5000K           LED Lumens © Tj 25°C         4647         4863         4959         6318         6212         6334           Luminaire Lumens © 52° Bearn         3580         3780         3820         5180         5093         5194           Typical CRI         85 (Optional 90)           MacAdams Ellipse         3 SDCM/MacAdam Steps           Beam Option         32°, 38°, 44°, 48°, 18° ELG, 26° ELG, 52° ELG (Extra Low Glare)           Performance           70% Lumen Maintenance © 50,000 Hrs (L70)           Luminaire Power         37.2w (1050mA @ 35.4V Nominal)         50w (1400mA @ 35.7V Nominal)           Connected Load         40.4w         55.1w |                             |
|--|-----------------------------|
| Colour Temperature         3000K         4000K         5000K         3000K         4000K         5000K           LED Lumens © Tj 25°C         4647         4863         4959         6318         6212         6334           Luminaire Lumens © 52° Beam         3580         3780         3820         5180         5093         5194           Typical CRI         85 (Optional 90)           MacAdams Ellipse         3 SDCM/MacAdam Steps           Beam Option         32°, 38°, 44°, 46°, 18° ELG, 26° ELG, 52° ELG (Extra Low Glare)           Performance           70% Lumen Maintenance © 50,000 Hrs (L70)           Luminaire Power         37.2w (1050mA © 35.4V Nominal)         50w (1400mA © 35.7V Nominal)           Connected Load         40.4w   | Version                     |
| LED Lumens @ Tj 25°C 4647 4863 4959 6318 6212 6334  Luminaire Lumens @ 52° Beam 3580 3780 3820 5180 5093 5194  Typical CRI 85 (Optional 90)  MacAdams Ellipse 3 SDCM/MacAdam Steps  Beam Option 32°, 38°, 44°, 46°, 18° ELG, 26° ELG, 52° ELG (Extra Low Glare)  Performance 70% Lumen Maintenance @ 50,000 Hrs (L70)  Luminaire Power 37.2w (1050mA @ 35.4V Nominal) 50w (1400mA @ 35.7V Nominal)  Connected Load 40.4w   | Colours                     |
| Luminaire Lumens @ 52° Beam 3580 3780 3820 5180 5093 5194  Typical CRI 85 (Optional 90)  MacAdams Ellipse 3 SDCM/MacAdam Steps  Beam Option 32°, 38°, 44°, 46°, 18° ELG, 26° ELG, 52° ELG (Extra Low Glare)  Performance 70% Lumen Maintenance © 50,000 Hrs (L70)  Luminaire Power 37.2w (1050mA @ 35.4V Nominal) 50w (1400mA @ 35.7V Nominal)  Connected Load 40.4w 555.1w  | Colour Temperature          |
| Typical CRI 85 (Optional 90)  MacAdams Ellipse 3 SDCM/MacAdam Steps  Beam Option 32°, 38°, 44°, 46°, 18° ELG, 26° ELG, 52° ELG (Extra Low Glare)  Performance 70% Lumen Maintenance © 50,000 Hrs (L70)  Luminaire Power 37.2w (1050mA © 35.4V Nominal) 50w (1400mA © 35.7V Nominal)  Connected Load 40.4w 55.1w  | LED Lumens @ Tj 25°C        |
| MacAdams Ellipse Beam Option 32°, 38°, 44°, 46°, 18° ELG, 26° ELG, 52° ELG (Extra Low Glare)  Performance 70% Lumen Maintenance © 50,000 Hrs (L70)  Luminaire Power 37.2w (1050mA © 35.4V Nominal)  Connected Load 40.4w 55.1w   | Luminaire Lumens @ 52° Beam |
| Beam Option 32°, 38°, 44°, 46°, 18° ELG, 26° ELG, 52° ELG (Extra Low Glare)  Performance 70% Lumen Maintenance © 50,000 Hrs (L70)  Luminaire Power 37.2w (1050mA © 35.4V Nominal) 50w (1400mA © 35.7V Nominal)  Connected Load 40.4w 55.1w   | Typical CRI                 |
| Performance 70% Lumen Maintenance © 50,000 Hrs (L70)  Luminaire Power 37.2w (1050mA © 35.4V Nominal) 50w (1400mA © 35.7V Nominal)  Connected Load 40.4w 55.1w  | MacAdams Ellipse            |
| Luminaire Power 37.2w (1050mA @ 35.4V Nominal) 50w (1400mA @ 35.7V Nominal)  Connected Load 40.4w 55.1w  | Beam Option                 |
| Connected Load 40.4w 55.1w   | Performance                 |
|  | Luminaire Power             |
| IP Rating IP40 (IP54 With Window)  | Connected Load              |
|  | IP Rating                   |
| Material Heat Sink - Extruded Aluminium, Bezel & Body - Cast Aluminium   | Material                    |
| Finish White, Black, Custom Colour by Special Order  | Finish                      |
| Power Supply  DALI Dimming: LPC-LCAI-501050  Non Dimming: LPC-LCI-501050  DALI Dimming: LPC-LCAI-501400  Non Dimming: LPC-LCAI-501400  | Power Supply                |
| Power Factor >0.9  | Power Factor                |
| Weight 930g (Fixed Recessed)   | Weight                      |
| Hole Cut Out 140mm Dia (Fixed), 180mm Dia (Adjustable)   | Hole Cut Out                |
| Mounting Options Fixed Recessed, Adjustable Recessed, Surface Mount, Suspended   | Mounting Options            |

## ORDERING CODES

