

PRODUCT SHEET L-7-LED SERIES



L-7/12-LED

SPECS/DETAILS

Red/White Array Circuit Board 12-Volt Operation **Attached Gooseneck (END Mount)** 1 x 1 x 3" Chassis with Rotary Switch 12" Pigtail

Wattage: 1.5 Watts Draw @ 12V: 150mA

Light Output @ 12": 398 Lux **Color Temperature: 4000K**

CRI: 85 Ra

Average Life @ 12V: 60,000 Hours

MODEL LIST

With Power Supply

L-7/12-LED - 12" Gooseneck L-7/18-LED - 18" Gooseneck

No Power Supply

L-7/12A-LED

L-7/18A-LED

With Euro Power Supply (Type C Plug)

L-7/12E-LED L-7/18E-LED

RECOMMENDED ACCESSORIES/PARTS

HTC – High Tension Clamp

MB - Magnetic Base

SM - Snap Mount

RAKIT - Rack Rail Bracket FDB - VESA Mount Bracket



Melbourne 03 9701 2500 Sydney 02 9737 8988

info@lightmoves.com.au www.lightmoves.com.au

© Littlite, LLC. Not to be reprinted without permission. Littlite reserves the right to change specifications and product descriptions at any time without prior written or oral notice.