

PUNCTOLED I

LED downlights



Areas of application

- Corridors
- Wardrobes
- Downlights

Product benefits

- High brightness thanks to LED technology
- Simple installation
- High-value design
- Energy-saving alternative to luminaires that use halogen lamps

Product features

- Dimmable (with suitable dimmers)
- Adjustable head
- Color temperature: 3,000 K
- Solid aluminum housing in white
- High-power LED
- Type of protection: IP33



For more information please contact

lightmoves (03) 9701 2500
info@lightmoves.com.au

138-146 Browns Rd, Noble Park VIC 3174

Product family datasheet

Technical data

Product description	Type of installation	Nominal wattage	Color temperature	Beam angle	Nominal voltage	Mains frequency
PUNCTOLED I 2x8.5 W	Recessed	8.5 W	3000 K	25 °	220...240 V	50/60 Hz
PUNCTOLED I 2x4.5 W	Recessed	4.5 W	3000 K	25 °	220...240 V	50/60 Hz
PUNCTOLED I 10.5 W	Recessed	10.5 W	3000 K	25 °	220...240 V	50/60 Hz

Product description	Luminous flux	Light color as per EN 12464-1	Color rendering index Ra	Length	Width	Diameter
PUNCTOLED I 2x8.5 W	450 lm	Warm white	≥ 80	85.0 mm	85.0 mm	85.0 mm
PUNCTOLED I 2x4.5 W	220 lm	Warm white	≥ 80	66.0 mm	66.0 mm	
PUNCTOLED I 10.5 W	625 lm	Warm white	≥ 80	98.0 mm	98.0 mm	

Product description	Height	Body material	Product color	Equipment	Adjustable	Dimmable
PUNCTOLED I 2x8.5 W	70.0 mm	Aluminium	White	LED	Yes	Yes
PUNCTOLED I 2x4.5 W	42.0 mm	Aluminium	White	LED	Yes	Yes
PUNCTOLED I 10.5 W	65.0 mm	Aluminium	White	LED	Yes	Yes

Product description	Type of connection	Protection class	Type of protection
PUNCTOLED I 2x8.5 W	Connector	II	IP33
PUNCTOLED I 2x4.5 W	Connector	II	IP33
PUNCTOLED I 10.5 W	Fixed (cutting terminal)	II	IP33

Product family datasheet

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

