


Date:	_Type:
Firm Name:	
Project:	

eW Reach Compact Powercore

Premium long-throw compact exterior LED floodlight with solid white light

Ordering Information

Select a color or color temperature to specify a complete configuration.



= Standard component

Standard Configuration

If you select a color temperature of 2700 K or 4000 K, your eW Reach Compact Powercore configuration is standard. Order a standard configuration using Item Number or Philips 12NC. Standard configurations are not subject to a minimum order quantities or extended production lead times.

Standard Configuration:

eW Reach Compact Powercore, 4000 K, CQC

Use Item Number 523-000084-23 or Philips 12NC 912400130290 (CQC)

Custom Configurations

If you select a color temperature other than 2700 K or 4000 K, your configuration is custom.

Minimum Order Quantity: 20 fixtures for each custom configuration Production Lead time: 12 weeks ARO (standard shipping options apply)

Custom Configuration:

Special, eW Reach Compact Powercore, 3000 K, CQC

(Contact your Philips Lighting Sales group with the product description for custom configurations.)

In North America contact: Philips Color Kinetics Sales, 888.385.5742 or sales@colorkinetics.com



eW Reach Compact Powercore Standard Configurations

Item	Туре		Item Number	Philips 12NC
eW Reach Compact Powercore Includes 6 ft (1.8 m) Leader Cable	2700 K	CQC	523-000084-20	912400130287
	4000 K	CQC	523-000084-23	912400130290









POWERCORE®

Accessories

Item	Туре	Item Number	Philips 12NC	
3 Conductor Replacement Leader Cable:	CE	108-000046-01	910503700621	
6 ft (1.8 m)				
4 Conductor Replacement Leader Cable (required to digitally dim unit, w/ DE Pro): 6 ft (1.8 m)	CE	108-000043-03	910503700454	
Data Enabler Pro (required to digitally dim unit)	PG21 / PG13 (metric size conduit)	106-000004-01	910503701211	
Spread Lens with bezel	8°	120-000068-05	910503700511	
	13°	120-000068-00	910503700506	
	23°	120-000068-01	910503700507	
	40°	120-000068-02	910503700508	
	63°	120-000068-03	910503700509	
	Asymmetric (5° x 17°)	120-000068-04	910503700510	

Use Item Number when ordering in North America.

Features

eW Reach Compact Powercore combines all the benefits of LED-based lighting in a compact fixture specifically designed for large-scale installations calling for high-quality white light, including commercial skyscrapers, casinos, large retail exteriors, bridges, piers, public monuments, and themed attractions. With levels of light output and projection never before achieved in a compact LED lighting fixture, eW Reach Compact Powercore delivers intense, energy-efficient output at a reasonable price, opening up new possibilities for exterior illumination. Standard configurations include a warm 2700 K and a cool 4000 K, with six additional color temperatures available, ranging from 3000 K to 6500 K.

- Unique split design supports diffuser combinations
- Unparalleled light output of over 10,000 **lumens**
- Universal power input range, directly from line
- Exchangeable spread lenses of 8°, 13°, 23°, 40°, 63°, and an asymmetric 5° x 17°
- Simple fixture positioning
- Industry-leading control

For detailed product information, please refer to the eW Reach Compact Powercore Product Guide at www.philipscolorkinetics.com/ls/ essentialwhite/ewreachcompact/

Sor more information on how to buy Philips Color Kinetics LED lighting systems, visit www.philipscolorkinetics. com/ls/howtobuy/



Philips Color Kinetics 3 Burlington Woods Drive Burlington, Massachusetts 01803 USA Tel 888.385.5742 Tel 617.423.9999 Fax 617.423.9998 www.philipscolorkinetics.com @ColorKinetics