

Product Specification Sheet

Arena High Performance Fresnel



A 2.0kW / 2.5kW Fresnel luminaire using a 250mm lens. Beam quality is excellent with a well-controlled flat even field with a distinct “white-blue” tint.

The Arena High Performance Fresnel offers superior light output, strength and industry leading performance.

Features

Leading performance for a theatre Fresnel due to 250mm diameter lens.

Wide range of beam angles: 9° - 56°.

Integrated safety bond rated for the luminaire.

Flat even beam with very little spill allows clean masking with barndoor flaps.

Adjustable yoke balance point.

Swing-down door for easy access to lamp or lens.

“Cool Touch Technology” – rear mouldings and large rear grab handle.

Your choice of GY16 lamp socket for CP72, 2.0kW lamp or G22 lamp socket for CP91 2.5kW or CP92 2.0kW lamp.

‘Posi-slide’ focus system with no metal to metal contact provides smooth focus movement.

Effective airflow maintains lower body temperature.

Constructed of pressure die-castings and aluminium extrusion.

Lamps: 220V-240V

GY16 lamp socket / 2000W

CP72

50,000 lumens 400 hours average life

G22 lamp socket / 2500W

CP91

65,000 lumens 400 hours average life

G22 lamp socket / 2000W

CP92

50,000 lumens 400 hours average life

Order Codes

10SF2520GY16

Arena H.P. Fresnel - GY16

10SF2525G22

Arena H.P. Fresnel - G22

20BDSF2025

Barndoor

20SM25

Lens safety mesh

20HC

Suspension hookclamp

Approvals

Fully tested and compliant to CE standards.

Supplied by:

lightmoves

Melbourne
03 9701 2500

Sydney
02 9737 8988

info@lightmoves.com.au

www.lightmoves.com.au

