Selecon

Product Specification Sheet Fresco LED Wall Washer



The Fresco LED Wall Washer is a specialist lighting tool for display and commercial lighting applications.

Providing an even wash of light, the Fresco LED Wall Washer is the ideal wall washer or subject flood.

Features

The body is engineered from a combination of aluminium pressure die castings. All power cables are internal to mount and body.

Visually smooth asymmetric beam. Fully blended light source - no fringing.

LED engine and precision designed reflector are recessed into the luminaire housing for best glare control commensurate with the beam angles provided.

Minimal power consumption (13W) and lower maintenance requirement than traditional halogen sources.

Passively cooled - no fans for silent operation

Positive, precise pan and tilt adjustment with allen lock off. Reference scales to record/ duplicate focus position.

Four flap barndoors to shape / mask the light beam, available to match luminaire colour or with the flap interior finished in black.

Comes with Selecon's three year warranty.

Approvals

CE Marked

Mounting Options

Universal track three circuit track adapter.

Ceiling mount plate, ridged 80mm x 20mm

1.0m cable tail, with or without ANZ plug 50mm half coupler and 1.0m cable tail, with or without ANZ plug





Ceiling rose mount

Track adapter

Power Supply Options

Local Dimming - non dimmed mains supply. Dali Dimming - non dimmed mains supply.

Wattage / Power Supply 13W / 220 – 240v (1100 Lumens) 17W / 220 – 240v (2000 Lumens)

Colour Temperature 3000K / 35,000hrs

CRI / Colour Consistency 95 / Within 3-Step MacAdam Ellipse

Choice of Output 1100lm or 2000lm

Colour Finish

White = PANTONE® 11-4800 Blanc de Blanc



Black

White



03 9701 2500

02 9737 8988

info@lightmoves.com.au

www.lightmoves.com.au

Order Codes

- 1 1100 lumens
- 2-2000 lumens
- $\mathsf{LD}-\mathsf{Local}\;\mathsf{Dim}-\mathsf{non}\text{-}\mathsf{dimmed}\;\mathsf{mains}\;\mathsf{input}$
- DD Dali Dim non-dimmed mains input (not available with Ceiling Rose, Half Coupler, or Flex mount)
- H 50mm Halfcoupler and 1.0m cable
- C Ceiling Rose
- G Global track adaptor standard option for track mount. Dali or local control
- T Eutrack adaptor non-standard option for track mount. Dali or local control.
- $E-eDali\ Track\ adaptor-custom\ adaptor\ for\ three\ circuit\ track-for\ installations\ using\ Dali\ on\ standard\ track.\ Please\ contact\ your\ sales\ representative.$
- 01 White
- 03 Black
- P Aust / NZ plug

Product Family	Light Source	Lumen Output	Control	Mounting	Paint Finish	Plug
FRS	LED	1	LD	Н	01	Р
		2	DD*	О	03	
				G		
				Т		
				F		
				Е		

IE: FRSLED1LDG01 = Fresco LED Wall Washer, 1100 lumens, Local Dimming,

Global Track adaptor, White Finish


* DALI Dimming version only available with Track adaptor Mounting (T,G,E)

Accessories Codes

FRSLEDBD01 White Fresco Wall Washer Barndoor FRSLEDBD01 Black Fresco Wall Washer Barndoor

ARLAKTOOL Allen key hand tool for Selecon display luminaires

Physical Data



Weight: 1.2 Kgs

Selecon reserves the right to change this product specification without notice (October 2015).