

ARES 75RG SM

SURFACE-MOUNT LED DOWNLIGHT • M-SERIES


11W

DESCRIPTION

Trim: Die-cast Aluminium (white standard)
Body: Die-cast Aluminium (white standard)
Safety Cover: Clear Glass
Reflector: Pure Anodised Aluminium 99.98%
Weight: 0.72kg
Dimensions: 260/135mm H x 100mm D

FEATURES

- Two models: 260mm or 135mm long
- 5-year Electrical System Warranty
- High Colour Consistency (MacAdam 3 SDCM)
- Passive Cooling
- Dimmable
- CRI >80



ORDERING CODE ¹	DESCRIPTION	POWER WATTAGE	LUMEN OUTPUT
111640SM-YY	ARES 75R SURFACE LED DOWNLIGHT 3000K V. NARROW	11	830
111641SM-YY	ARES 75R SURFACE LED DOWNLIGHT 3000K NARROW	11	799
111642SM-YY	ARES 75R SURFACE LED DOWNLIGHT 3000K MEDIUM	11	821
111643SM-YY	ARES 75R SURFACE LED DOWNLIGHT 3000K WIDE	11	809
111644SM-YY	ARES 75R SURFACE LED DOWNLIGHT 4000K V. NARROW	11	873
111645SM-YY	ARES 75R SURFACE LED DOWNLIGHT 4000K NARROW	11	848
111646SM-YY	ARES 75R SURFACE LED DOWNLIGHT 4000K MEDIUM	11	887
111647SM-YY	ARES 75R SURFACE LED DOWNLIGHT 4000K WIDE	11	864

¹ Ordering codes:
 YY = Control Options (PD = Phase Dim, ND = Non-Dim,
 DA = DALI, DMX = DMX512)

Specifications subject to change without notice.

