ELLE





DESCRIPTION

The Elle is an ultra high-output compact LED floodlight designed for architectural feature and general lighting applications.

FEATURES

Collimators High precision optics available in narrow, medium, wide, and elliptical angles to suit every application.

Lens Transparent, weatherproof, and shock-resistant. **Housing** Anodised aluminium.

Cable Separate UV-stabilised power and data cables. **Adjustable Bracket** Allows the mounting of the luminaire in any working position.















DYNAMIC OUTDOOR LED FLOODLIGHT



SPECIFICATIONS

Housing

Anodised aluminium

Ingress Protection

IP65

Control

DMX512, RDM

(Remote Device Management)
Onboard thermal management
with RDM monitoring and
current (brightness) reduction
in the event of overheating.

LEDs

CREE

Elle 20: 24 LEDs

Elle 40: 48 LEDs

Elle 60: 72 LEDs

LED Optics

Specify at time of order: 10°, 30°, 10° x 60°, 90°, 110°.

LED Colours

Single colour:

Red, Green, Blue, Amber, Cool

White, Warm White.

Also available in variable white and variable colour (RGBA).

Power

180-260VAC 50/60Hz single

phase

Elle 20: 40W

Elle 40: 72W

Elle 60: 108W

Accessories

Stainless steel mounting

brackets

Accessories not included

DMX controller

DIMENSIONS





