FIM

MULTI-FUNCTIONAL LED BAR



DESCRIPTION

The FIM is a high-output compact linear LED bar designed for architectural feature and general lighting applications.

A mains-voltage version of the Mini Athena MkII, and powered by the latest Philips Luxeon Rebel LEDs, the FIM is available in single colour, warm/cool white, or RGB colour-changing. It's perfect for lighting architectural features, grazing walls, lighting passages, stairways, windows, and much more.

Fully dimmable with integral DMX and RDM for remote address-setting and diagnostics, the FIM is the perfect choice for special effect and architectural feature lighting.

FEATURES

Collimators High precision optics available in narrow, medium, wide, and elliptical angles to suit every application.

Lens Transparent, weatherproof, and shock-resistant. **Housing** Anodised aluminium, custom colours available*. **Cable** Combined UV-stabilised outdoor power/data cable with custom 7-pin in/out connectors for easy installation. Simply daisy-chain together.

Adjustable Bracket Allows the mounting of the luminaire in any working position.







LED RG
COLOURS COLO
AVAILABLE MIXII









FIM

MULTI-FUNCTIONAL LED BAR



SPECIFICATIONS

Housing

Aluminium

- anodised or powder-coated

Ingress Protection

IP66

Control

DMX512. RDM

(Remote Device Management) Onboard thermal management with RDM monitoring and current (brightness) reduction in the event of overheating.

LEDs

Philips Lumileds LUXEON

Rebel LEDs

FIM 600: 18 LEDs FIM 900: 27 LEDs FIM 1200: 36 LEDs

LED Optics

Specify at time of order: 6°, 20°, 30°, 45°, 9 x 45° Also available with no optics.

LED Colours

Single colour:

Red, Green, Blue, Amber, Cool

White, Warm White.

Also available in variable white and variable colour (RGB).

Power

90-250VAC 50/60Hz single phase with over-voltage, overload, and short-circuit protection

FIM 600: 22W FIM 900: 33W FIM 1200: 44W


Accessories

Mounting brackets

Accessories not included

DMX controller

DIMENSIONS



ModelLengthFIM 600655mmFIM 900955mmFIM 12001255mm



