



Sylverline Essential 300



Dimensions (mm)



Photometric curve



Code table

product	size	finishing	control	voltage	color	optics
ESS	03	AN	R	048	SW	NB
ESS= Sylverline Essential	03= 300mm	AN= Anodised Aluminium	R= With regulator	048= 48VDC	SW = 2200 K WW= 3000 K NW = 4000 K CW = 6000 K MR = Red MG = Green MB = Blue MA = Amber RT = RGB RW = RGB+White RA = RGB+Amber TW = SW to CW	NB = Narrow beam MB = Medium beam WB = Wide beam EN = Elliptical narrow FL = Flood optics EW = Elliptical wide

Specification are subject to change without notice.
rev . Datasheet Sylverline Essential 300 1115EN

Space Cannon Australia Pty Ltd
1/169 Beavers Road | Northcote | Vic | 3070
T (+61 3) 9486 5366 | sales@spacecannon.com.au
www.spacecannon.com.au

Technical specification

Source:
High power LED
LED Count:
9 (mono, RGB, TW), 12 (RGBW, RGBA)
LED life time:
>50,000 hrs (L70 B50)
Source flux:
1465 lm (NW)
Luminaire efficiency:
70 lm/W (NW_NB)
Input power:
17W
Supply voltage:
48 VDC
Driver:
Remote power supply and integrated current regulator
Insulation class:
III
Protections:
Short circuit, overload, over voltage and thermal
Colour:
White (2200K to 6000K), RGB, RGBW, RGBA, Tunable White (2200K to 6000K), Red, Green, Blue, Amber
Emission:
PC precision optics 8°, 30°, 45°, 8°x45°, 100° and 40°x75° reflector
Working position:
Any
Fixation:
1 bracket with 3 elongated holes Ø6.2mm and 1 hole Ø6.2mm
IP rating:
IP65 and IP67
IK rating:
IK 08
Storage:
-50°C to +80°C
Control:
No control (On/Off) or via control accessories (DMX-512A)
Connection:
M12 Connector (IP67)
Construction:
Anodised aluminum extruded body, AISI 316 stainless steel bracket, pressure compensation valve, UV-stable polycarbonate cover, hermetic sealing by silicone gaskets, stainless steel screws
Weight:
0.8 kg

Authorised Dealer