

# CONTROL 24 CV

## CONSTANT VOLTAGE LED DRIVER

CV

### PRODUCT OVERVIEW

The Control 24 is a DMX/RDM controller for 12 or 24V constant voltage LEDs. With a maximum output power of 600W, the Control 24 Power LED provides eight (8) RGB outputs, each with fuse protection.

Control 24 is available in 2 versions, built in power supply or external power supply.

New SpaceDim high resolution and high speed technology enables smooth and full-range dimming of LEDs down to zero, simulating traditional tungsten dimming curves. This enables a more natural effect, and is perfect for all applications including architectural, theatrical, film and TV work.

Remote Device Management (RDM) is a protocol enhancement to DMX512 that allows bi-directional communications between light fixtures and lighting consoles or RDM specific software over a standard DMX line.

### FEATURES

- Internal power supplies (600VA max.)
- Terminal strip input and output connectors
- 2 main indication LEDs (RED - Power ON, GREEN - DMX Receive)
- Available in wall-mount or 19" rack-mount
- In-built test programs

### RDM FEATURES\*

**Discovery Mode:** Locates all RDM-compliant devices on the DMX line.

**Identifier Mode:** Fixtures connected to driver will flash to show location.

**Remote Addressing:** Allows you to set the DMX address remotely without the need to set dip switches.

**Global Master/Slave Mode:** (32-channel mode where every 4th DMX channel is a master, enabling convenient global colour control).

**Stand-alone Mode:** Pre-programmed chase patterns with speed and fade control.

### Internal soft-patching

\* DMX/RDM Tool Box required



### SPECIFICATIONS

**Input Voltage:** 100-240VAC

**Power:** 640VA (max.)

**Dimensions (mm):**

270 W x 530 L x 70 H (Wall-mount)

483 W x 240 D x 88 H (Rack-mount)

**Mounting Options:**

Desktop | Wall | 19" Equipment Rack | Ceiling

**DMX Mode:** RGB 24 channels

**DMX Input/Output:** XLR 5-pin

**Output Channels:** 24

**Driving Capacity:** PWM - 12VDC or 24VDC typical (specify at ordering)

**Temperature:** 0-50°C

 **spacecannon**  
Australia

[www.spacecannon.com.au](http://www.spacecannon.com.au)